



Physical Water Conditioning, Correcting, Balancing since 2008.

Chemical-Free, Energy-Free, Maintenance-Free.

## Wellbolt™ Product Information and Technical Specs

**Purpose-built to go down to the source**

### OVERVIEW

Wellbolt™ is a specialized, heavier-weight adaptation of the Rainbolt™ that's specifically designed to install down wells or at intakes from tanked or ponded water. Its weight helps the assembly stay where it's needed. And the Magnation Water Technology within Rainbolt™ keeps it working for decades with no maintenance, no electrical power and no consumables.

Magnation Wellbolt units fit 4-inch pipe diameter, anodized aluminum body, installed inline at the well, prior to pump system. As a powerful and effective chemical-free water softener, Wellbolt™ reduces or eliminates scale, specifically supports reduction in iron bacteria, scale and corrosion control. For use in any irrigated water environment. Well unit installed below pump as well casing.

### FEATURES

- Available in 316 stainless steel and aerospace anodized aluminum
- Zero chemicals, energy, consumables or maintenance
- Passive, in-line system
- Zero by-products
- 2-year satisfaction money-back guarantee
- Proudly designed and made in USA with 100% US materials

### APPLICATIONS

- Agriculture
- Turfgrass irrigation
- Drilling
- Industry
- Residential



# Wellbolt™ Technical Specs

## Wells, Industrial

PRODUCT CODE	MATERIAL	INTERNAL DIAMETER	EXTERNAL DIAMETER	LENGTH	WEIGHT	FLOW RATE	RETAIL PRICING
MG-WELL-4-SS	SS	4 in	6 in	9 in	30 lbs	up to 700 gpm	\$7,650
		101.6 mm	152.4 mm	228.6 mm	13.6 kg	up to 2650 L/min	
MG-WELL-6-SS	SS	6 in	7 in	13 in	50 lbs	up to 1000 gpm	\$10,825
		152.4 mm		177.8 mm	330.2 mm	22.7 kg up to 3785 L/min	
MG-WELL-8-SS	SS	8 in	9 in	13 in	85 lbs	up to 1900 gpm	\$12,480
		203.2 mm	228.6 mm	330.2 mm	38.6 kg	up to 7192 L/min	
MG-WELL-10-SS	SS	10 in	11 in	13 in	110 lbs	up to 2000 gpm	\$14,180
		254 mm	279.4 mm	330.2 mm	50 kg	up to 7570 L/min	
MG-WELL-12-SS	SS	12 in	13 in	13 in	130 lbs	up to 3000 gpm	\$16,825
		304.8 mm	330.2 mm	330.2 mm	60 kg	up to 11355 L/min	
MG-WELL-4-AL	AL	4 in	6 in	9 in	11 lbs	up to 700 gpm	\$6,050
		101.6 mm	152.4 mm	228.6 mm	5 kg	up to 2650 L/min	
MG-WELL-6-AL	AL	6 in	7 in	13 in	27 lbs	up to 1000 gpm	\$8,480
		152.4 mm		177.8 mm	330.2 mm	12.2 kg up to 3785 L/min	
MG-WELL-8-AL	AL	8 in	9 in	13 in	35 lbs	up to 1900 gpm	\$10,180
		203.2 mm	228.6 mm	330.2 mm	15.9 kg	up to 7192 L/min	
MG-WELL-10-AL	AL	10 in	11 in	13 in	49 lbs	up to 2000 gpm	\$12,710
		254 mm	279.4 mm	330.2 mm	22.2 kg	up to 7570 L/min	
MG-WELL-12-AL	AL	12 in	13 in	13 in	60 lbs	up to 3000 gpm	\$14,710
		304.8 mm	330.2 mm	330.2 mm	27.2 kg	up to 11355 L/min	

